C) Cons wherein said control part controls said color space converting part to reduce bit numbers for [each color signal] <u>video</u> signals transferred through said interface part <u>correspondingly</u> with a selected one of said predetermined, diverse color spaces.

SUBDE

10. (Twice-Amended) An image pickup apparatus comprising:

an image sensor for photo-electrically converting a picked-up Object image into an electrical signal;

a video signal generating part for forming a video signal from the electrical signal;

a color space converting part <u>having a plurality of</u>

<u>predetermined</u>, <u>diverse color spaces selectable therein</u> for

converting a color space of the video signal; and

an interface part for externally transferring the video signal,

wherein said color space converting part is controlled by a control apparatus connected to said interface part to reduce bit numbers for [each color signal] video signals transferred through said interface part correspondingly with a selected one of said predetermined, diverse color spaces.

SUBOF

20. (Twice-Amended) An image pickup unit comprising:

image pickup means for picking up an optical image to form a picked-up image signal;

interface means for performing communication with an external signal processing apparatus; and

compression control means <u>having a plurality of</u>
predetermined, diverse bit reduction data for controlling and

C3 cont c3 cond reducing bit numbers for [each color signal] <u>picked-up signals</u> transferred according to a control signal supplied from said external signal processing apparatus through said interface means and indicative of a selected one of said plurality of predetermined diverse bit number reduction data.

SUBD4

24. (Twice-Amended) A picked-up image signal processing means comprising:

C4 Concl interface means for performing communication with an image pickup unit including image pickup means for picking up an optical image to form a picked-up image signal and a plurality of predetermined, diverse bit number reduction data therein; and

transmission control means for transmitting to said image pickup unit through said interface means a control signal for controlling and reducing bit number of [each color signal] <u>picked-up image signals</u> transferred through said interface means, <u>said control signal being indicative of a selected one of said predetermined</u>, <u>diverse bit number reduction data</u>.

Enter the following additional claim.

SURDS

28. An image pickup system adapted for use with any one of plural, diverse type image display devices, comprising:

an image pickup apparatus including an image sensor for photo-electrically converting a picked-up object image into an electrical signal, a video signal generating part for forming a video signal from the electrical signal, and a color space converting part having a plurality of predetermined, diverse color

C5 Curit